



**POLYPLUS 18**  
**Metallic floor finish**

**DESCRIPTION**

POLYPLUS 18 is a concentrated acrylic metallic floor finish for low frequency maintenance floor. Based on acrylic polymers, it contains 18% solid matters, to give high resistance to detergents, wear, black marks, scuffs and water. It possesses slip resistance properties exceeds ASTM D 2047 standard. Formulated for professional use, it adapt to all type of flooring for an optimal long-lasting shine.



**ADVANTAGES**

1. High resistance to detergents, wear and other
2. Possesses slip properties
3. Adapt to all type of flooring

**TECHNICAL DATA**

pH (as is) .....	8,5 – 9,0
Density (20 °C) .....	1,024 g/cc
Colour .....	White liquid
Fragrance .....	Light odor
Biodegradability .....	Complete
Flash Point .....	More than 95 °C
Freezing Stability .....	Keep out from freezing
Degradability determined in accordance with OECD no. 301D.	

**DIRECTIONS**

In order to bring a surface back to its original condition:

1. Strip the floor with DECAPLUS floor stripper.
2. Rinse and neutralise and let the surface dry completely.
3. With a finish mop, apply two or three coats of POLYPLUS 18 depending on the flooring's porosity and humidity.
4. Allow 20 to 25 minutes drying time between coats or more time if you have more humidity.

Whenever the surface brightness is somewhat worn out; clean the floor and spray-buff with a polishing floor product.

**UNICA CANADA INC.**

90, J.-Armand Bombardier, Boucherville (Québec) J4B 8N4

Tél.: 450.655.8168 • Fax: 450.655.4411

Courriel: unica@unicacanada.com • Visitez notre site web [www.unicacanada.com](http://www.unicacanada.com)