



**POLYPLUS 25**  
**U.H.S. thermoplastic floor finish**

**DESCRIPTION**

POLYTHERMO 25 is an ultra concentrated ultra high speed / high-speed floor finish for automatic machine. It contains a high content level of solid matters (25%), to give high resistance to detergents, wear, black marks, scuffs and water. Its maintenance is easy and it possesses slip resistance properties meets ASTM D 2047 standard. Formulated for professional use, it doesn't need a sealer and is suitable on all types of floor surfaces as well as all maintenance methods.



**ADVANTAGES**

1. High resistance to detergents, wear and other
2. Possesses slip properties
3. Suitable on all type of floor surfaces

**TECHNICAL DATA**

pH (as is) .....	8,5 - 9,0
Density (20°C).....	1,034 g/cc
Coefficient Friction (ASTM D2047) .....	> 0.60
Colour.....	White liquid
Fragrance.....	Light odor
Characteristic.....	Very gloss
Flash Point .....	More than 95°C
Freezing Stability .....	Keep out from freezing
Degradability determined in accordance with OECD no. 301D.	

**DIRECTIONS**

In order to bring a surface back to its original condition:

1. Strip the floor with DECAPLUS floor stripper.
2. Rinse and neutralise and let the surface dry completely.
3. With a finish mop, apply two or three coats of POLYTHERMO 25 depending on the flooring's porosity and humidity.
4. Allow 20 to 25 minutes drying time between coats or more time if you have more humidity.

For use in food plants: Not for use on food contact surfaces. Avoid food contamination during use and storage.

**UNICA CANADA INC.**

90, J.-Armand Bombardier, Boucherville (Québec) J4B 8N4

Tél.: 450.655.8188 • Fax: 450.655.4411

Courriel: unica@unicacanada.com • Visitez notre site web [www.unicacanada.com](http://www.unicacanada.com)