TECHNICAL SHEET

POLYPLUS 25
Metallic floor finish

DESCRIPTION:
POLYPLUS 25 is an ultra concentrated acrylic metallic floor finish for low frequency maintenance floor. Based on acrylic polymers, it contains 25% solid matters, to give high resistance to detergents, wear, black marks, scratches, and water. It has superior anti-slip properties D 2047 standard. Formulated for professional use, it adapts to all type of flooring for an optimal long-lasting shine.

ADVANTAGES:
1. High resistance to detergents, wear and other
2. Possesses anti-slip properties
3. Adapt to all type of flooring

TECHNICAL DATA

pH (as is)	8,5 – 9,0
Density (20°C)	1,034 g/cc
Coefficient Friction (ASTM D2047)	0.63
Colour	White liquid
Fragrance	Slight odor
Characteristic	Very glossy finish
Flash Point	More than 95°C
Freezing Stability	Keep from freezing

Degradability determined in accordance with OECD no. 301D.

DIRECTIONS:
In order to bring a surface back to its original condition:

1. Strip the floor with **DECAPLUS** floor stripper.
2. Rinse and neutralise and let the surface dry completely.
3. With a finish mop, apply two or three coats of **POLYPLUS 25** depending on the flooring's porosity and humidity.
4. Let it dry completely, about 45 to 55 minutes, before applying another coat. High temperature, humidity, and a thicker coat may increase drying time.

Whenever the surface brightness is somewhat worn out; clean the floor and spray-buff with a 50: 50 **POLYPLUS 25** with water.

UNICA CANADA INC.
90, J.-Armand Bombardier, Boucherville (Québec) J4B 8N4
Tél.: 450.655.8168 • Fax: 450.655.4411
Courriel: unica@unicacanada.com • **Visitez notre site web www.unicacanada.com**